

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 06-306248

(43)Date of publication of application : 01.11.1994

(51)Int.Cl.

C08L 33/08

C08L 75/04

(21)Application number : 05-119001

(71)Applicant : SANYO CHEM IND LTD

(22)Date of filing : 21.04.1993

(72)Inventor : OMORI HIDEKI
SHIMADA MOTOO
AKIYAMA HAJIME

(54) COMPOSITE RESIN COMPOSITION FOR SLUSH MOLDING

(57)Abstract:

PURPOSE: To provide the composition composed of an acrylic resin and a thermoplastic polyurethane resin, having excellent moldability, flexibility, heat-resistance, light-resistance and surface-aging stability and useful for automotive interior trim, etc.

CONSTITUTION: The objective composition is composed of (A) an acrylic resin, preferably an acrylic resin having active hydrogen and (B) a thermoplastic polyurethane resin, preferably a resin produced by reacting an organic polydiisocyanate, a polymeric polyol, a chain extender and a termination agent in the component A. The weight ratio of A/B is preferably (20-80)/(80-20).

LEGAL STATUS

[Date of request for examination]

11.09.1997

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

2958599

[Date of registration]

30.07.1999

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]